

[illegible]

剖分轴承座十字轴式向联轴器基本参数和主要尺寸 (JB/T 3241-1991)

型号	回转 直径 D mm	额定 转矩 Tn kN•m	疲劳 转矩 Tf kN•m	轴线折 角 β (°)	伸缩 量 S (mm)	尺 寸 (mm)										转动 惯量 I kg. m ²		质量 m kg	
						Lmin	D1 js11	D2 H7	D3	E	E1	b×h	H1	L1	n-d				
																Lmin	增长 100	Lmin	增长 100
SWP160A	160	16	8	≤10	50	660	140	95	114	15	4	20×12	6	85	6-13	0.13	0.0059	47	2.1
SWP180A	180	20	10	≤10	60	752	155	105	121	15	4	24×14	7	95	6-15	0.22	0.0072	60	2.3
SWP200A	200	31.5	16	≤10	70	823	175	125	127	17	5	28×16	8	110	8-15	0.37	0.0114	81	3.4
SWP225A	225	40	20	≤10	76	933	196	135	152	20	5	32×18	9	130	8-17	0.63	0.0290	109	6.6
SWP250A	250	63	31.5	≤10	80	978	218	150	168	25	5	40×25	125	135	8-19	1.02	0.0407	147	7.3
SWP285A	285	90	45	≤10	100	1133	245	170	194	27	7	40×30	15	150	8-21	217	0.0702	241	9.4
SWP315A	315	140	63	≤10	110	1250	280	185	219	32	7	40×30	15	170	10-23	3.86	0.1144	322	12.0
SWP350A	350	180	90	≤10	120	1380	310	210	245	35	8	50×32	16	185	10-23	6.66	0.1663	428	13.6
SWP390A	390	250	112	≤10	120	1495	345	235	273	40	3	70×36	18	205	10-25	11.53	0.2695	566	18.0
SWP435A	435	355	160	≤10	150	1710	385	255	299	42	10	80×40	20	235	16-28	21.81	0.3645	932	20.0
SWP480A	480	450	224	≤10	170	1910	425	275	351	47	12	90×45	225	265	16-31	38.04	0.7028	1294	28.0
SWP550A	550	710	315	≤10	190	2135	492	320	402	50	12	100×45	225	290	16-31	61.28	1.1842	1744	357
SWP600A	600	1000	500	≤10	210	2580	544	380	450	55	15	90×55	27.5	360	22-34	98.63	1.7159	2330	40.5
SWP640A	640	1250	630	≤10	230	2685	575	385	480	60	15	100×60	30	385	18-38	167.67	2.3080	3153	48.3