



基本尺寸和参数 Basic dimensions and parameters of the locking assemblies, type Z4

规格 sizes	基本尺寸					内六角螺钉			额定负荷		Pf	Pf	G (kg)
	Basic dimensions					In hex agons screws			Rated load		N/mm ²	N/mm ²	
d×D	d	D	I	L	L1	规格 sizes	数量 OT	MA N.m	Ft KN	Mt KN.m			
70×120	70	120	56	62	74	M12	8	145	197	6.85	201	117	3.3
80×130	80	130	56	62	74	M12	10	145	291	11.65	263	162	3.7
90×140	90	140	56	62	74	M12	12	145	290	13.00	234	150	4.0
100×160	100	160	74	80	94	M14	15	230	389	19.70	213	133	7.2
110×170	110	170	74	80	94	M14	15	230	483	22.60	242	157	7.7
120×180	120	180	74	80	94	M14	15	230	482	28.90	222	148	8.3
125×185	125	185	74	80	94	M14	15	230	480	30.00	212	143	8.5
130×190	130	190	74	80	94	M14	15	230	480	31.20	205	140	8.8
140×200	140	200	74	80	94	M14	18	230	574	40.20	227	159	9.3
150×210	150	210	74	80	94	M14	18	230	572	42.90	212	152	10.0
160×230	160	230	88	94	110	M16	18	355	800	64.00	227	158	14.9
170×240	170	240	88	94	110	M16	18	355	795	67.80	214	152	15.7
180×250	180	250	88	94	110	M16	21	355	923	83.00	235	170	16.4
190×260	190	260	88	94	110	M16	21	355	921	88.00	223	163	17.2
200×270	200	270	88	94	110	M16	24	355	1050	105.0	242	179	18.8
210×290	210	290	110	110	134	M18	20	485	1118	117.0	197	143	23.0
220×300	220	300	110	110	134	M18	21	485	1120	123.0	189	138	27.7
240×320	240	320	110	110	134	M18	24	485	1280	153.0	198	148	29.8
250×330	250	330	110	110	134	M18	27	485	1282	160.0	205	157	31.0
260×340	260	340	110	116	134	M18	27	485	1430	186.0	205	157	32.0
280×370	280	370	130	136	156	M20	24	690	1650	230.0	192	145	46.0
300×390	300	390	130	136	156	M20	24	690	1650	245.0	179	138	49.0

注：Z4 型胀紧联结套螺钉的机械性能等级为 12.9 级。