



基本尺寸和参数 Basic dimensions and parameters of the locking assemblies,type Z7A

规格 sizes d×D	基本尺寸 Basic dimensions						六角头螺栓 Hexagon head bolts			额定负荷 Rated load		G l(Kg)
	d	D	I	H	dw	e	规格 d1 sizes	数量 n QTY	MA N.m	Mt KN.m	Ft KN	
	mm											
125×185	125	185	40	52	95	6	M10	8	58	242	11.5	
	125	185	40	52	100	6	M10	8	58	260	13	6
140×220	125	185	40	52	105	6	M10	8	58	276	14.5	
	140	220	40	52	110	6	M10	10	58	291	16	
140×220	140	220	40	52	120	6	M10	10	58	330	20	8
	140	220	40	52	125	6	M10	10	58	352	22	
155×245	155	245	40	52	130	6	M10	12	58	385	25	
	155	245	40	52	135	6	M10	12	58	427	28.8	10
155×245	155	245	40	52	140	6	M10	12	58	464	32.5	
	165	260	46	62	135	8	M12	10	100	474	32	
165×260	165	260	46	62	140	8	M12	10	100	507	32.5	14
	165	260	46	62	145	8	M12	10	100	538	39	
175×275	175	275	46	62	145	8	M12	10	100	538	39	
	175	275	46	62	150	8	M12	10	100	573	43	16
175×275	175	275	46	62	155	8	M12	10	100	606	47	
	185	295	46	62	155	8	M12	12	100	632	49	
185×295	185	295	46	62	160	8	M12	12	100	662	53	20
	185	295	46	62	165	8	M12	12	100	691	57	
195×315	195	315	56	72	165	8	M12	15	100	800	66	
	195	315	56	72	170	8	M12	15	100	835	71	27
195×315	195	315	56	72	175	8	M12	15	100	869	76	
	220	345	66	84	180	9	M16	9	240	978	88	
220×345	220	345	66	84	190	9	M16	9	240	1063	101	35
	220	345	66	84	200	9	M16	9	240	1140	114	
240×370	240	370	66	84	200	9	M16	12	240	1200	120	
	240	370	66	84	210	9	M16	12	240	1276	134	44
240×370	240	370	66	84	215	9	M16	12	240	1312	141	
	260	395	72	90	220	9	M16	12	240	1309	144	
260×395	260	395	72	90	230	9	M16	12	240	1384	159	48
	260	395	72	90	235	9	M16	12	240	1421	167	

规格 sizes	基本尺寸 Basic dimensions						六角头螺栓 He× agonheadbolts			额定负荷 Ratedload			G (kg)
	d	D	l	H	dw	e	规格 ch sizes	数量 n QTY	MA N.m	Mt KN.m	Ft KN		
d×D	mm												
	280	425	84	104	230	10	M16	15	240	1478	170		
280×425	280	425	84	104	240	10	M16	15	240	1583	190	60	
	280	425	84	104	250	10	M16	15	240	1680	210		
	300	460	84	104	250	10	M16	16	240	1740	213		
300×460	300	460	84	104	260	10	M16	16	240	1800	234	75	
	300	460	84	104	270	10	M16	16	240	1889	255		
	320	495	84	106	270	11	M16	18	240	1955	264		
320×495	320	495	84	106	280	11	M16	18	240	2036	285	84	
	320	495	84	106	290	11	M16	18	240	2076	301		
	340	535	84	106	290	11	M16	20	240	2193	318		
340×535	340	535	84	106	300	11	M16	20	240	2300	345	100	
	340	535	84	106	305	11	M16	20	240	2354	359		
	360	555	100	122	300	11	M20	15	470	2547	382		
360×555	360	555	100	122	310	11	M20	15	470	2645	410	125	
	360	555	100	122	320	11	M20	15	470	2738	438		
	390	595	112	136	330	12	M20	18	470	3091	510		
390×595	390	595	112	136	340	12	M20	18	470	3194	543	156	
	390	595	112	136	350	12	M20	18	470	3291	576		
	420	630	120	144	350	12	M20	20	470	3371	590		
420×630	420	630	120	144	360	12	M20	20	470	3500	630	185	
	420	630	120	144	370	12	M20	20	470	3620	670		
	460	685	132	158	390	13	M20	24	470	3949	770		
460×685	460	685	132	158	400	13	M20	24	470	4300	860	235	
	460	685	132	158	410	13	M20	24	470	4634	950		
	500	750	152	178	420	13	M20	30	470	4881	1025		
500×750	500	750	152	178	430	13	M20	30	470	5233	1125	320	
	500	750	152	178	440	13	M20	30	470	5568	1225		

注：Z7A 型胀紧联结套螺钉的机械性能等级为 10.9 级。